

MATERIAL SAFETY DATA SHEET (MSDS)

Cal-CM Plus Limestone Standard Prilled

SECTION I	IDENTITY (As used on label and list)
------------------	---

Manufacturing Facility:
ART WILSON CO.
PO BOX 20160
CARSON CITY, NV 89721-0160

CAL-CM PLUS
LIMESTONE STANDARD PRILLED

SECTION II	HAZARDOUS INGREDIENTS / IDENTITY INFORMATION
-------------------	---

Hazardous components (specific chemical identity, common names OSHA PEL / ACGIH TLV / other limits recommended % optional)

NONE

SECTION III	PHYSICAL / CHEMICAL CHARACTERISTICS
--------------------	--

Boiling Point	NONE	Bulk Density(pounds/cubic foot)	68-76
Vapor Pressure (mm Hg)	NONE	Melting Point	1,330° C
Vapor Density Air =1)	NONE	Evaporation Rate (Butyl Acetate = 1)	NONE
Solubility in Water	0.0006%		
Appearance and Odor			

SECTION IV	FIRE AND EXPLOSION HAZARD DATA
-------------------	---------------------------------------

Flash Point (method used)

NON-FLAMMABLE

SECTION V	REACTIVITY DATA
------------------	------------------------

Stability	STABLE	Conditions to Avoid	NONE
Incompatibility (materials to avoid)	ACIDS	Hazardous Decomposition or By-Products	NONE
Hazardous Polymerization	WILL NOT OCCUR	Conditions to Avoid	NONE

SECTION VI	HEALTH HAZARD DATA
-------------------	---------------------------

NON-HAZARDOUS

SECTION VII	PRECAUTIONS FOR SAFE HANDLING AND USE
--------------------	--

Steps to be taken in case material is released or spilled
Waste disposal method
Precautions to be taken in handling and storing

SWEEP UP AND REMOVE
TRANSPORT TO LAND FILL OR SPREAD ON AGRICULTURAL ACREAGE
WEAR DUST MASK IN DUSTING CONDITION

SECTION VIII	CONTROL MEASURES
---------------------	-------------------------

Respiratory Protections (specify)

NOT REQUIRED